

TDS: SKIMCOAT



PRODUCT NAME

SKIMCOAT

DATE CREATED

01/01/2021

LAST REVIEWED 09/02/2021

DESCRIPTION

QUICKWALL **SKIMCOAT** is a highly modified flexible 2 pack polymer cement for :

1. Preparing most substrates as a base coat for selected Quickwall Applied Finishes.
2. Obliterating defective joints in Hebel Blocks, Hebel Power Panels, Masonry Blocks, Bricks, etc.
3. A bonding base coat to Polystyrene and Polyurethane sheets reinforced with alkali resistant mesh.
4. A base coat plaster for QUICKCLAD wall cladding systems or white set plaster.

GRADES

Regular Skimcoat - thin film base coat – excellent adhesion

High-Build Skimcoat for filling deep joints, 2-4mm build

QuickClad Skimcoat for QuickClad Systems – Fibre reinforced

Traditional Coarse – floatable, light weight, high build base coat

SPECIAL FEATURES

- Will not go drummy like sand / cement render often does.
- Will not delaminate like acrylic coatings / acrylic render often does.
- Not effected by humidity like high build acrylic coatings are.
- High Impact, Flexural, Mechanical and Abrasion strengths.
- Unequaled bond to most substrates. Permanent base coat.
- Excellent protection for single skin construction.
- Excellent freeze thaw ability and exterior weathering.
- Resistant to most chemicals, no shrinkage.
- Non - combustible, Ease of workability / application.
- Bond to Ceramic Tiles with increased 1:1 Quickwall Polymer ratio.

SUITABLE SURFACES

Masonry Block

QuickClad Styrene – (Quickclad Skim only)

Painted Surfaces – Suitable with increased polymer.

Refer to Polymer Specification sheet for polymer ratios on substrates

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.
Extended 15 year guarantee for our 15L Aquaseal products.

SPECIFICATION

- 1st Coat: Apply Quickwall **SKIMCOAT**
- 2nd Coat: Apply Selected QUICK FINISH
- 3rd Coat: Apply 1 coat of AQUASEAL membrane paint
- 4th Coat: Apply 1 coat of AQUASEAL membrane paint