

TDS: SANDSTONE



PRODUCT NAME

**SANDSTONE TEXTURED
FINISHES**

DATE CREATED

01/01/2021

LAST REVIEWED 10/02/2021

DESCRIPTION

QUICKWALL **SANDSTONE** mimics the face of a freshly cut sandstone block. Quickwall SANDSTONE is generally applied over Quickwall SKIMCOAT to prepare the substrate.

Quickwall SANDSTONE is a 2 pack, polymer modified, mineral based wall coating which can be trowel or machine applied.

Quickwall SANDSTONE economically obliterates defective substrates and is excellent for the protection and decoration of single skin masonry walls. Unlike natural sandstone, Quickwall SANDSTONE exhibits a dense final finish and optimises dirt rejection after painting.

GRADES

1.5 mm, 2.0 mm and 3.0 mm

SUITABLE FOR

- Single Skin Masonry Blocks
- Clay Bricks
- Concrete
- Tilt-up Panels
- Quick Clad over Skim Coat
- Polystyrene over Skim Coat
- Quickwall Building Systems
- Hebel Panels
- Hebel Blocks

SPECIAL FEATURES

- Will not go drummy like sand / cement render often does.
- Does not delaminate, peel, blister or bubble like most acrylic coatings.
- Can be applied to dry or damp substrates.
- Will not wash off with wind driven rainwater after approx.. 20 minutes of application.
- Environment friendly and easy to use in any climate.
- Fast application provides early completion schedules.
- A permanent tough durable attractive and popular finish.

APPLICATION

Even Substrates: Apply Quickwall SKIMCOAT prior to **QUICKTROWEL**, or consult a representative.

Uneven Substrates: Apply Quickwall HIGH BUILD SKIMCOAT prior to **QUICKTROWEL**.

PAINTTING

The substrate can be painted after 48 hours under normal conditions. Paint with Quickwall Aquaseal Membrane paint– *refer to Aquaseal Specification Sheet for equivalent.*

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION

1st Coat: Apply Quickwall SKIMCOAT

2nd Coat: Apply Selected **QUICKTROWEL**

3rd Coat: Apply 1 coat of AQUASEAL membrane paint

4th Coat: Apply 1 coat of AQUASEAL membrane paint