

# TDS: TRADITIONAL RENDER



PRODUCT NAME

**TRADITIONAL RENDER:  
AVAILABLE IN COARSE OR  
FINE**

DATE CREATED

01/01/2021

LAST REVIEWED 10/02/2021

## DESCRIPTION

**TRADITIONAL RENDER** is a dry polymer modified dual purpose, floatable, traditional cement render for:

- (A) Obtaining a finished coat - traditional sponged finish render, or
- (B) Preparing most substrates as a base coat.\*

## SURFACE PREPARATION

Ensure substrate to be coated is clean and free of dirt, dust, oil grease or any loose material.

## FINISH COAT APPLICATION

As a finish coat of 10mm build and over, polymer is not essential, however is recommended for a stronger more adhesive finish at 8:1

- Pour approximately 4 litres of clean water into a clean empty 20 litre pail. Option to add 500ml of Quickwall Polymer.
- Slowly add **TRADITIONAL RENDER** to the water and mix with slow speed / high torque drill using GPML 130mm mixer. **Note that high speed mixing or extended mixing time will deteriorate the application and usage of the product.**
- Mix the product to a workable consistency ready for application, adding more polymer if required.
- Apply to substrate with trowel and level off flat with trowel.
- Allow to semi-dry before using a float and sponge to create required finish.

## BASE COAT OPTION

**TRADITIONAL RENDER** can be used as a base coat, when Quickwall Polymer is added at a ratio of 6:1 water:polymer. Traditional Render Coarse is ideal for correcting uneven substrates.

**WARNING:** TRADITIONAL RENDER IS **NOT SUITABLE AS A BASE COAT\*** FOR **POLYSTYRENE SYSTEMS OR EPS SYSTEMS**

WHEN THERE IS NO POLYMER BEING USED TRADITIONAL RENDER MUST BE APPLIED TO A **MINIMUM OF 10mm.**

## PAINTING

Allow 48 hours for product to dry before painting (under normal circumstances).

Paint with Quickwall Aquaseal Membrane paint– *refer to Aquaseal Specification Sheet for equivalent.*

## COVERAGE

As a base or finish coat : 5 – 10 m<sup>2</sup> is expected per bag depending on the substrate, application and finishing technique

## GUARANTEE

Seven years when applied by an Approved Applicator and in accordance to Quickwall specification.

## SPECIFICATION

### Traditional Render as **BASE COAT**

- 1<sup>st</sup> coat    Apply Quickwall **TRADITIONAL RENDER**
- 2<sup>nd</sup> coat    Apply selected Quick Finish
- 3<sup>rd</sup> coat    1 coat of Aquaseal membrane paint
- 4<sup>th</sup> coat    1 coat of Aquaseal membrane paint

### Traditional Render as **FINISH COAT**

- 1<sup>st</sup> coat    Apply **TRADITIONAL RENDER**
- 2<sup>nd</sup> coat    Optional - Apply **TRADITIONAL RENDER**
- 3<sup>rd</sup> coat    Apply Aquaseal membrane paint
- 4<sup>th</sup> coat    Apply Aquaseal membrane paint