

TDS: QUICKSPRAY



PRODUCT NAME

QUICKSPRAY

DATE CREATED

01/01/2021

LAST REVIEWED 10/02/2021

DESCRIPTION

QUICKWALL **QUICKSPRAY** offers a multitude of finishes from Stippled, Super Fine, English Coarse, American Stucco, Tear drop and many more to suit the designer's vision.

QUICKSPRAY can be used in seamless wall finishes, trim features, designer motifs, feature stripes, architraves and shadow lines.

QUICKSPRAY is excellent for redressing existing substrates, and can be used a one coat system over flat surfaces such as concrete panels etc.

QUICKSPRAY can be either supplied in a polymer modified mineral system or full acrylic to suit the application.

GRADES

Fine

Medium

Course

SUITABLE FOR

- Bricks
- Concrete
- Single skin masonry blocks
- Hebel products
- QuickClad
- Cement sheet Quickwall fire safe foam
- Polystyrene

APPLICATION

Even Substrates: Apply **QUICKSPRAY** direct to the substrate

Uneven Substrates: Apply QUICKWALL SKIMCOAT prior to the **QUICKSPRAY** finish.

SPECIAL FEATURES

- Obliterates substandard substrates.
- Apply to damp or dry substrates.
- Will not bubble, blister or go drummy.
- Exterior and Interior grades.
- Not affected by high humidity.
- Can be applied with machine hopper gun or dual gravity gun.

4th Step: Spray apply Quickwall Quickcrete top coat – Plaster Plus White - with selected colour additive, using a hopper gun.

5th Step: Apply Hi Tech Summer Sealer by roller

6th Step: Apply Hi Tech Summer Sealer by roller

* If using an acrylic sealer apply a 3rd coat.

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Ten years for mineral and Seven for tinted Acrylic, when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION

1st Coat: Apply Quickwall SKIMCOAT

2nd Coat: Apply Quickwall **QUICKSPRAY**

3rd Coat: Apply Quickwall AQUASEAL membrane paint

4th Coat: Apply Quickwall AQUASEAL membrane paint