

TDS: QUICKROLL



PRODUCT NAME

QUICKROLL

DATE CREATED

01/01/2021

LAST REVIEWED 15/02/2021

DESCRIPTION

QUICKROLL is a seamless roller or spray-applied wall finish with texture ranging from fine to coarse dependent on application technique, tools and viscosity of the product. **QUICKROLL** provides an economical, long lasting finish with excellent fungi, bacteria and algae protection. Excellent UV resistance and elastomeric qualities to bridge fine cracks.

GRADES

Black Roller = Low Build Blue Roller = Medium Build

Yellow roller = High Build

DISPENSING

10 litre, 20 litre & 200 litre packs.

COVERAGE

1 x 20 litre pail covers (approx.) 30-40 m² as a fine finish, and less for coarser finishes. Spread rate will be affected by the porosity of the substrate and application technique, therefore we recommend priming and experimenting to determine an accurate spread rate.

SUITABLE FOR

- Bricks
- AAC
- Concrete
- Cement sheet
- Masonry Blocks
- Plaster board

APPLICATION

Uneven Substrates: Apply Quickwall SKIMCOAT to masonry surfaces prior to priming the substrate with Quickwall Primer. Apply **QUICKROLL** topcoat and complete with 1 coat of AquaSeal Membrane paint– refer to AquaSeal Specification Sheet for equivalent.

Even Substrates: Fill air holes with Quickwall Jointing Compound, sand flat, seal with Quickwall Primer and apply **QUICKROLL** direct to the substrate, finish with Quickwall Aquaseal membrane paint.

SPECIAL FEATURES

An economical, versatile, user-friendly roll-on finish that may be colour tinted closely to the topcoat. By selecting the appropriate roller sleeve (shown above) the nominated build is achieved.

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Seven years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION:

- 1st Coat: Apply Quickwall PRIMER
- 2nd Coat: Apply Quickwall QUICKROLL
- 3rd Coat: Apply 1 coat Quickwall AQUASEAL membrane paint