

TDS: STIPPLE TEX



PRODUCT NAME

STIPPLE TEX

DATE CREATED

01/01/2021

LAST REVIEWED 15/02/2021

DESCRIPTION

STIPPLE TEX is best known for its crows foot stipple effect to beautify ceilings. It has the ability to hide off form concrete ceiling imperfections or joint lines and general impaired patches. **STIPPLE TEX** dries to a smooth rounded random stipple. Simply apply with a course yellow roller sleeve, or finish with a crows foot Stipple brush.

DISPENSING

10 litre & 20 litre packs.

COVERAGE

1 x 20 litre pail covers approx. 33m² depending on the porosity of the substrate, equipment, rollers etc.

APPLICATION

- **STIPPLE TEX** can be applied with combs / sponges / brush strokes /trowels etc. to achieve designer ceilings.
- Seal substrate with Quickwall Primer and apply direct to the sealed substrate.
- For uneven substrates or joints apply Quickwall SKIMCOAT, allow to dry and seal prior to the **STIPPLE TEX** application.

SPECIAL FEATURES

- **STIPPLE TEX** is user friendly and maintains good wet edge properties.
- Material is light weight and bonds to most substrates.
- Contains excellent biocides to protect against fungi, bacteria and algae formation even in hot humid tropical environments.
- May be applied with gravity hand held hopper guns or vermiculite spraying machines to provide the spray on splatter finishes from fine to medium and coarse builds.

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Seven years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION:

- 1st Coat: Apply Quickwall PRIMER
- 2nd Coat: Apply Quickwall **STIPPLE TEX**
- 3rd Coat: Apply 1 coat FLAT CEILING WHITE
- 4th Coat: Apply 1 coat FLAT CEILING WHITE