

# QUICK SEAL

## SOLVENT BASED CLEAR EXTERIOR SEALER

Sealer



<b>DESCRIPTION</b>	QUICKWALL <b>QUICKSEAL</b> is a solvent borne clear sealer.
<b>SUITABLE FOR</b>	Generally used for clear glazing exterior surfaces such as floors, bricks, pavers, pre-coloured concrete concourses, walls, exposed aggregate finishes and spray on tiles to provide a protective coating and moisture barrier against the elements.
<b>CLEANUP</b>	<b>QUICK SEAL</b> tools can be washed in xylene with <i>care taken using protective eye wear.</i>
<b>DILUTIONS</b>	Where lower solids are required to improve penetration in the first preparation coat, xylene is the preferred solvent to reduce the solids and achieve maximum penetration.
<b>VENTILATION</b>	All areas (particularly where <b>QUICK SEAL</b> is applied indoors), should be adequately ventilated or fan forced air should be provided.
<b>CAUTIONS</b>	<ul style="list-style-type: none"><li>⊗ <b>Do Not</b> smoke while applying <b>QUICK SEAL</b> material.</li><li>⊗ <b>Do Not</b> use open flame directly over the containers.</li><li>⊗ <b>Do Not</b> apply <b>QUICK SEAL</b> to damp substrates or where any traces of moisture may be present to avoid a milky appearance being bound into the coating.</li><li>⊗ <b>Always</b> use only what is required and replace the sealed lid immediately after de-cantering the required quantity.</li></ul>
<b>HAZARDOUS CHEMICAL</b>	Transportation of <b>QUICK SEAL</b> is marked with the <i>Hazardous chemical identification sticker.</i>
<b>NOTES</b>	Apply a minimum of two coats for best results. Dry times are fast but dependant on the ambient temperature.  Rollers that go hard overnight will regenerate when placed back into fresh <b>QUICK SEAL.</b>
<b>SPECIFICATION</b>	<p>1<sup>st</sup> Coat: Apply Quickwall <b>QUICK SEAL</b> to a dry substrate. Allow to dry.</p> <p>2<sup>nd</sup> Coat: Apply Quickwall <b>QUICK SEAL</b> before any impurities become lodged or dropped onto the 1<sup>st</sup> coat.</p> <p>3<sup>rd</sup> Coat: Apply 1 coat of <b>QUICK SEAL</b> as optional higher gloss and for additional wear characteristics.</p> <p>4<sup>th</sup> Coat: Apply 1 coat of <b>QUICK SEAL</b> as optional higher gloss and for additional wear characteristics.</p>