

# TDS: ACRYLIC QUICKTROWEL



PRODUCT NAME

**ACRYLIC QUICKTROWEL**

DATE CREATED

01/01/2021

LAST REVIEWED 29/03/2023

## DESCRIPTION

The general appearance of ACRYLIC QUICKTROWEL is similar to that of Quickwall's seamless polymer modified mineral based QuickTrowel vertical scratch coating system. Available in 1.5 mm, 2mm and 3mm grain increments.

## SUITABLE FOR

Substrates that experience movement such as cement sheet cladding fixed to steel stud frame walls. (Under sunny conditions the cement sheet expands in the opposite direction to steel stud frame walls, therefore the enhanced flexibility of ACRYLIC QUICKTROWEL is ideal to withstand reasonable movement.)

## APPLICATION

1. Apply QW PRIMER.
2. Flush and set all joints with QW Jointing Compound.
3. While wet place 50mm wide alkali resistant QUICKCLAD mesh over joints. Trowel additional Jointing Compound over reinforcing mesh, feather out and allow to dry to a flat finish.
4. Option to rectify undulations on substrate It is preferred by Quickwall that an application of regular SKIMCOAT at 2:1 polymer be applied over substrate and joints prior to finish coat.
5. Apply ACRYLIC QUICKTROWEL.
6. Apply 2 coats of QW AQUASEAL.

## SUBSTRATES

Fibre-cement sheets must be properly fixed in accordance to the manufacturer's specifications prior to the ACRYLIC QUICKTROWEL application. (See Spec Sheets on 'New & Existing Cement Sheet' and 'Jointing Compound'.) After preparation, the substrate must be dry before applying ACRYLIC QUICKTROWEL. Rendered substrates or Quickwall Skimcoated substrates over bricks, blocks or concrete will be flat and free from undulations.

## SPECIAL FEATURES

The product is environment and applicator friendly, exhibiting good algae, fungi and UV resistance.

## NOTE

ACRYLIC QUICKTROWEL will be top-coated with at least 2 coats of Aquaseal Membrane paint– refer to Aquaseal Specification Sheet for equivalent. The unethical practice of applying any acrylic coatings without membrane top-coating is Not Acceptable and should be avoided.

## GUARANTEE

Seven years when applied by an Approved Applicator and in accordance to Quickwall specification.

## SPECIFICATION:

1st Coat: Apply Quickwall PRIMER

2nd Coat: Apply Quickwall SKIMCOAT (recommended)

3rd Coat: Apply Quickwall Acrylic QUICKTROWEL

4th Coat: Apply Quickwall AQUASEAL membrane paint

5th Coat: Apply Quickwall AQUASEAL membrane paint