

# TDS: ACRYLIC TUSCANI



PRODUCT NAME  
DATE CREATED

**ACRYLIC TUSCANI**  
01/01/2021

LAST REVIEWED 29/03/2023

## DESCRIPTION

When applied over practically any properly prepared substrate, QUICKWALL TUSCANI will provide a touch of Venice. Where the specifier's vision requires special decorative and protective finishes, TUSCANI will provide decades of protection to the substrate.

## APPLICATION

**Trowel:** Apply by "stainless steel" trowel and while wet, re-trowel in a circular pattern with a 817P plastic trowel to provide a pre-coloured adobe effect with a controlled smooth high to low wall finish.

**Brush:** Apply by spray, roll 1 freehand trowel or TUSCANI brush to the substrate. Finish from the top of the wall with vertical downward sweeps using a soft nylon broom to provide a pre-coloured touch of Venice.

***TUSCANI is generally tinted close to the topcoat colour. Usually only one final coat of membrane is then required.***

## SPECIAL FEATURES

- Excellent water resistance.
- Environment and user-friendly acrylic product.
- Fully formulated with bactericides, algacides, and fungicides.
- This faux finish allows the specifier, applicator and client freedom to bend the rules and find that exclusive seamless designer finish.

## GUARANTEE

Seven years when applied by an Approved Applicator and in accordance to Quickwall specification

## SPECIFICATION

1st Coat: Apply Quickwall PRIMER to the properly prepared substrate

2nd Coat: Apply Quickwall TUSCANI

3rd Coat: Apply Quickwall AQUASEAL 100% acrylic membrane paint