

# TDS: JOINTING COMPOUND



PRODUCT NAME

**JOINTING COMPOUND  
NON SOLVENT BASED  
MULTI USE JOINT FILLER**

DATE CREATED

01/01/2021

LAST REVIEWED 28/03/2023

## DESCRIPTION

QUICKWALL JOINTING COMPOUND is a tough universal water based filler compound ready to use straight from the pail for both external and internal applications to bridge joints on expanding and retracting substrates. It is a flexible co-polymer jointing compound

## SUITABLE FOR

QUICKWALL JOINTING COMPOUND will retain its elastomeric ability enabling it to be used in many applications such as:

- Flush out joints in pre cast concrete slabs pre-stressed flooring systems
- Cement sheet abutments • Gap filler to off form concrete
- Patch repair with alkali resistant fibreglass mesh to joints.
- Expansion joint filler

## SPECIAL FEATURES

- Minimum shrinkage and can be worked thinly to a feather-edge without powdering or breaking down.
- Has excellent keying ability.
- Is compatible to all Quickwall construction products and virtually all substrate building materials.
- Extremely resistant to all forms of fungicides or bacteria and application in tropical environs have not suffered after many years of extended use.
- Environment and applicator friendly.

## WASH UP/CARE

Wash up in water.

## APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

## SPECIFICATION

1<sup>st</sup> Coat: Apply Quickwall SKIMCOAT

2<sup>nd</sup> Coat: Apply Selected **QUICKSAND**

3<sup>rd</sup> Coat: Apply 1 coat of AQUASEAL membrane paint

4<sup>th</sup> Coat: Apply 1 coat of AQUASEAL membrane paint