

TDS: MASONRY RENDER 120



PRODUCT NAME
DATE CREATED

MASONRY RENDER 120
01/01/2021

LAST REVIEWED 30/03/2023

DESCRIPTION

QW Masonry Render 120 is a pre-bonded, polymer modified cement based render which requires only the addition of clean water. This product contains a unique powdered bonding agent (glue) to work with the binding power of the cement, (i.e. a 'dual binding system'), which ultimately:

- Speeds up and simplifies the on-site mixing process;
- Increases adhesion to all suitable, properly prepared substrates;
- Guarantees the correct amount of bond every time – whether applied by hand or machine;
- Provides the same quality, integrity and longevity – whether applied by hand or machine.

QW Masonry Render 120 is suitable for interior and exterior use, providing an excellent surface for the application of acrylic textures and paints.

ADVANTAGES

QW Masonry Render 120 provides:

- A non-tacky formulation for easier application.
- An extended 'hang time' for greater productivity and high early hardness.
- Great 'straightening qualities' via the use of darbies.
- Tear resistant screedability.
- Excellent come-back qualities for easy floating and finishing.

TYPICAL USES

QW Masonry Render 120 is generally used where a consistent high quality render product is required. They can be used as a full render coating in single or multiple coats – applied between 7-10mm thick per coat and 'screeded flat'. Alternatively, they can be used as a thin section render applied between 4-8 mm thick, which can then either be screeded flat or allowed to follow the undulations of the substrate.

Either technique can be finished ready to receive acrylic render/trowel/rollon textures. Otherwise, the render can be floated and sponge finished ready to receive two coats of roll-on finishing product such as Quickwall Aquaseal membrane paint.

SPECIAL FEATURE

The unique dual binder system ensures that every bag mixed correctly for application over clay brick and concrete blocks, is guaranteed to have high integrity.

SUITABLE SUBSTRATES

- Concrete blocks
- Concrete slab edges
- Concrete tilt panels
- Off-form concrete
- Clay bricks

PAINTING

The substrate can be painted after 24 hours under normal conditions. Paint with Quickwall Aquaseal paint or equivalent

GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION

1st Coat: Apply QW MASONRY RENDER 120

2nd Coat: Apply 1 coat of Aquaseal membrane paint

3rd Coat: Apply 1 coat of Aquaseal membrane paint