

TDS: PLASTER PLUS



PRODUCT NAME

PLASTER PLUS

DATE CREATED

01/01/2021

LAST REVIEWED 10/02/2021

DESCRIPTION

Similar to a sponge finished (scrub fine) render in appearance, **PLASTER PLUS** is a 2 pack, polymer modified, cement based render. Because of its superior adhesion, PLASTER PLUS can be thin film, free-hand applied over Quickwall keyed SKIMCOAT to a smooth undulating sanded finish and top coated with Quickwall Aquaseal Membrane paint– *refer to Aquaseal Specification Sheet for equivalent.*

SUITABLE FOR

- Bricks
- Prepared Concrete
- Single Skin Masonry Blocks
- Quick Clad – Over Skim Coat
- Quick Panel
- Hebel Products

SPECIAL FEATURES

- Faster than solid plaster to apply, covering more surface area daily for the same number of applicators.
- Incorporated waterproofing additives.
- Excellent for packing thick sections in one application, maintains internal moisture for thin set plaster while curing, even suction providing extended control of finishing techniques.
- Highly modified cement. Environment friendly, wash up in water.

APPLICATION

Even Substrates: Splash coat the substrate with Quickwall SKIMCOAT prior to the **PLASTER PLUS** application.

Uneven Substrates: Apply 3 mm minimum thickness of a selected Quickwall SKIMCOAT to the substrate, leaving a keyed rough flat base coat, prior to PLASTER PLUS.

NOTE: PLASTER PLUS can be applied by plaster / mortar machines without blockages commonly experienced with standard cement plaster.

POLYMER

Polymer ratio can be modified to suit the application and is recommended at between 4:1 to 5:1 over masonry substrates.

PAINTING

The substrate can be painted after 48 hours under normal conditions. Paint with Quickwall Aquaseal Membrane paint– *refer to Aquaseal Specification Sheet for equivalent. Or Quickwall Clear Seal where a natural finish is required*

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION

- 1st Coat: Apply Quickwall SKIMCOAT
- 2nd Coat: Apply Quickwall **PLASTER PLUS**
- 3rd Coat: Apply 1 Coat of AQUASEAL membrane paint or Quickwall Clear Seal
- 4th Coat: Apply 1 coat of AQUASEAL membrane paint or Quickwall Clear Seal