

TDS: QUICKGRIP ADHESIVE



PRODUCT NAME
DATE CREATED

QUICKGRIP ADHESIVE
01/01/2021

LAST REVIEWED 29/03/2023

DESCRIPTION

QUICKWALL QUICKGRIP is an acrylic copolymer putty adhesive..

SUITABLE FOR

Designed with extended binding time, QUICKGRIP bonds QUICKCLAD rigid fire retardant insulation boards to timber or metal studs. The 12 hour bond time is retarded to allow extended working times while working with the rigid sheets. This allows the installer sufficient time to position the sheets accurately prior to mechanically fixing. QUICKGRIP will be used on all horizontal and vertical joints to insure positive mechanical strengths at the joints.

SPECIAL FEATURES

- Excellent resistance from microbial attacks and the adhesive remains flexible for extended long life.
- No harmful solvents are used in the production of QUICKGRIP.
- Applicator and environment friendly with a shelf life of approximately twelve months.

COVERAGE

Bulk 20 litre pails provide an economical alternative compared to small, expensive adhesive tubes. 1x 20 litre QUICKGRIP adhesive pail is generally sufficient to spot adhere approximately 200 m2 of wall area

WASH UP/CARE

Wash up tools in water, however, should QUICKGRIP droppings be overlooked the surplus can be mechanically scrapped from the substrate and reduced with xylene. Wash up hands in water.

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

SPECIFICATION

Step 1: Insure QUICKGRIP is spot applied to a clean and oil-free substrate.

Step 2: Apply Quickwall QUICKGRIP in spots with a spatula.

Step 3: Press rigid insulation board against stud with a slight sideway movement prior to fixing.

Step 4: Apply QUICKGRIP with a spatula to all joints prior to mechanical fixing. Replace lid on container when not in use.